

# operating


### **OPERATING MANUAL**

#### ASSEMBLY/USAGE LOOK SERIES RAISED TOILET SEATS


FOR MODELS:

1662 2" Seat 1663 2" Seat with Lid 1664 4" Seat 1665 4" Seat with Lid

#### **WARNINGS**



**Never** overtighten the clamps as this could cause damage to the toilet bowl or the seat itself.



**Check** your raised toilet seat every week to ensure all clamps are securely tightened.



**Only** use the raised toilet seat on toilets that meet the specifications. Ensure the seat rests well on the toilet frame.




DO NOT exceed weight capacity!

DO NOT USE THE RAISED TOILET SEAT IF THERE ARE ANY CRACKS OR DAMAGED COMPONENTS!

#### **CARE AND USE**



**DO NOT** use chlorine bleach or abrasive cleansers. To clean, wipe down with a damp cloth using a mild detergent only.



**This** raised toilet seat will only fit standard toilet seats (approximate size:  $12\frac{3}{4}$ " x  $10\frac{1}{4}$ "/32cm x 26cm).



**Supervision** or assistance when using seats is recommended for users with limited mobility.

## READ ALL WARNINGS CAREFULLY

KEEP THIS INFORMATION FOR FUTURE REFERENCE


#### **ASSEMBLY**



Before installing your raised toilet seat, make sure your toilet is dry and dirt free.




No tools are required.



Lift the existing seat and place the raised toilet seat onto the toilet bowl.



Position the front lip against the front of the toilet bowl.



Turn both adjustment knobs clockwise until the rubber buffers touch the toilet bowl.

IF YOU HAVE ANY PROBLEMS OR REQUIRE ASSISTANCE WITH THIS PRODUCT PLEASE CALL:

613-723-6734



MADE IN CHINA

